

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

1. (Currently amended) A demultiplexer, comprising:  
a single molded piece comprising an integrated first section, second section, third section, and diffraction grating,  
the [[a]] first section capable of receiving a WDM beam,  
[[a]] the diffraction grating integrally formed in the first section,  
the WDM beam being directed onto the internal surface of  
the diffraction grating, and the diffraction grating providing  
angularly separated beams on the external surface of the  
diffraction grating; and  
~~a second section integrally formed with the first section; and~~  
~~a third section integrally formed with the second section,~~ the third  
section positioned relative to the first section to receive  
spatially separated light beams of a selected diffraction  
order from the diffraction grating, ~~wherein the first section,~~  
~~the second section, the third section, and the diffraction~~  
~~grating are integrally formed as a single molded piece.~~
2. (Previously presented) The demultiplexer of Claim 1, further including  
a reflective surface integrally formed on the first section that directs the WDM  
beam received into the first section onto a bottom surface of the diffraction  
grating.
3. (Previously presented) The demultiplexer of Claim 2, wherein

the reflective surface is coated external to the first section with thin film to enhance internal reflection of the WDM beam.

4. (Previously presented) The demultiplexer of Claim 2, wherein the reflective surface is coated with a reflective film.
5. (Previously presented) The demultiplexer of Claim 4, wherein the reflective film is a gold film.
6. (Previously presented) The demultiplexer of Claim 4, wherein the reflective film is a silver film.
7. (Previously presented) The demultiplexer of Claim 1, wherein the first section includes an integrally formed collimating lens integrally formed into the single piece, the integrally formed collimating lens collimating the WDM beam received from an optical fiber.
8. (Previously presented) The demultiplexer of Claim 7, further including a barrel integrally formed into the single piece with the first section, the barrel capable of receiving an optical fiber and aligning the optical fiber with the collimating lens.
9. (Previously presented) The demultiplexer of Claim 7, further including a post integrally formed into the single piece with the first section, the post capable of receiving a barrel,

the barrel capable of receiving an optical fiber and aligning the optical fiber with the collimating lens.

10. (Original) The demultiplexer of Claim 8, wherein the barrel includes a fiber access and a fiber stop.
11. (Original) The demultiplexer of Claim 9, wherein the barrel includes a fiber access and a fiber stop.
12. (Original) The demultiplexer of Claim 1, wherein the third section includes a focusing lens.
13. (Original) The demultiplexer of Claim 12, wherein the third section further includes a support around the focusing lens.
14. (Original) The demultiplexer of Claim 13, wherein a detector array can be mounted on the support so that the spatially separated beams are directed onto individual detectors of the detector array.
15. (Previously presented) The demultiplexer of Claim 13, wherein optical fibers are arranged to receive individual ones of the spatially separated beams.
- 16-22. (Canceled)

23. (Previously presented) A demultiplexer, comprising:
- means for separating an input light beam into constituent parts with a molded single piece component;
  - means for detecting the constituent parts from the molded single piece component;
  - means for aligning the means for separating with the means for detecting.